

E Series

# E1050TW



With all its advanced features, this camera gives you great pictures with just a touch.

Compact and stylish, the GE E1050TW redefines the term "feature-rich." For starters, it offers the latest touch-screen panel technology that makes it fun and easy to take fabulous photos. Plus, the aspheric all-glass lens provides an ultra sharp image. The E1050TW is our first camera to offer direct HDTV output.

With a spacious 3-inch high-resolution LCD screen (230,400 pixels), photo playback is a delightful experience. The GE E1050TW comes with the latest auto-brightness LCD technology that ensures perfect screen visibility both indoors and outdoors.

Featuring a comprehensive 10-megapixel resolution, 5x optical zoom, 4.5x digital zoom, 22.5x combined zoom, and a 28mm wide angle lens, you won't find a camera that's more versatile ... from tight close-ups to wide group shots.

Within the 23.8mm slim body design is a host of advanced features, including: In-Camera Panorama Stitching, Smile Detection, Blink Detection, Face Detection, Electronic Image Stabilization, Red-Eye Removal and an amazing 1280x720 MPEG-4 movie recording capability.

Hold the E1050TW and see for yourself all it has to offer. Then you'll understand how this camera is taking point-and-shoot models to a whole new level.

Shown in black.  
Also available:



Red



Silver



Exclusive  
Digital Camera  
Licensee

General Imaging™

With all its advanced features, this camera gives you great pictures with just a touch.

Effective Image Sensor Pixels		10.1 Megapixels
Image Sensor		10.7 Megapixels [1/2.33" Charge Coupled Device (CCD) ]
Lens	Focal Length F =	5.1 mm (Wide) – 25.5 mm (Tele)
	[35mm film equivalent]	[28 mm (Wide) – 140 mm (Tele) ]
	F number	F3.3 (Wide) – F5.1 (Tele)
	Lens Construction	9 elements in 8 groups
	Optical Zoom	5X
Focusing Range		Normal: 60cm~∞ ;(Tele)80cm~∞ Macro: (Wide) 5cm~60cm
Anti-Handshake		Electronic Image Stabilization
Digital Zoom		4.5X digital zoom (Combined Zoom: 22.5X)
Number of Recording Pixels	Still Image	10MP: 3648×2736, (3:2)9MP: 3648×2432, 8MP: 3264 x 2448 (16:9)7MP: 3648×2052, 5MP: 2560×1920, 3MP: 2048×1536 0.3MP: 640×480
	Movie	1280×720pixels: 25fps/15fps, 640×480pixels: 30fps/15fps, 320×240pixels: 30fps/15fps
Image Compression		Best , Fine , Normal
DCF , DPOF (Ver1.1) Support		Yes
File Format	Still Image	Exif2.2 (JPEG)
	Movie	Image Compression: MPEG4, Audio: G.711 (Monoaural)
	Audio	WAVE (Monoaural) (Max 60 seconds)
Shooting Modes		Auto, Manual, Image Stabilization, Movie, Scene (Sport, Children, Indoor, Leaf, Snow, Sunset, Fireworks, Glass, Museum, Landscape, Night Landscape, Night Portrait), Panorama, Portrait
Start-Up Time		1.5 sec.
Detection Features		Face, Smile and Blink
Red-Eye Removal		Yes
Viewfinder		-
LCD Screen		3.0 inch (230,400 pixels) LTPS ( low-temperature polycrystalline silicon) TFT color LCD (Touch Panel) Self-regulation brightness in the sun
ISO Sensitivity		Auto, ISO80/100/200/400/800/1600
AF Method		Single AF, Multi-AF (TTL 9-point), Face-Detection, AF Assist Beam (On / Off)
Light Metering Method		Artificial Intelligence AE (Ai AE), Center-Weighted Average, Spot (Fixed to center of frame)
Exposure Control Method		ProgramAE (AE-lock available)
Exposure Compensation		± 2 EV in 1/3 Step increments
Shutter Speed		4 ~ 1/2000 second (Manual 30s)
Continuous Shooting		Approx. 1.8 fps (Large/Fine Mode)
Playback Modes		Single Photo, Index (4 / 9 thumbnails), Slide Show, Movie (Slow-Motion possible), Zoom (Approx. 2X~8X), Audio , Histogram Display
White Balance Control		Auto (AWB), Daylight, Cloudy, Incandescent, Fluorescent , Fluorescent CWF , Manual
Internal Flash (Shooting Range)		Auto / Red-Eye Reduction / Forced Flash / No Flash / Slow Synchro / Red-Eye Reduction+Slow Synchro Shooting Range - Wide: Approx. 0.3m~3.2m / Tele: Approx. 0.3m~2.1m (ISO 400)
Recording Media		Internal Memory: 26MB SD Card / SDHC Card (Up to 4GB support)
Other Features		PictBridge , ExifPrint Support , Multi-language Support (23 languages) , HD Still Output
Jacks		USB2.0 / AV-OUT (Integrated Proprietary Connector), HDTV
Power		Rechargeable Lithium-ion Battery GB-40 , 3.7V 1050mAh
Shooting Capability (Battery Performance)		Approx. 200 shots (based on CIPA Standards)
Operation Environment		Temperature: 0~40°C, Humidity: 0~90%
Body Material		Metal cover
Dimensions (W x H x D)		3.6 inch Width × 2.2 inch Height × .9 inch Depth (93mm Width × 58mm Height × 23.8mm Depth)
Weight		5.1 oz. (Approx. 145g) (Body only)
Supplied Accessories		Rechargeable Lithium-ion Battery, Battery Charger, USB Cable, AV Cable, Wrist Strap, CD-ROM, Manual, Quick Start Guide, Quick Feature Guide, Warranty Card

(Design and specifications are subject to change without notice)