

E Series

E1235



Megapixels aren't the only thing about this camera that are huge.

The GE E1235 is a top-of-the-line point-and-shoot camera that gives you the features and megapixel resolution you'd expect from a professional camera. The E1235 comes with an amazing 12-megapixel resolution, so it's easy to see why the E1235 is the premium model in the stylish E series.

The stunning GE E1235 comes with a high-quality metal body design, 3x optical zoom, 4.5x digital zoom, 13.5x combined zoom and a 2.7" high-resolution LCD screen (230,400 pixels), which means you won't have to squint to see what you're capturing. Plus, the E1235 offers our latest auto-brightness LCD technology that ensures perfect screen visibility both indoors and outdoors, and our aspheric all-glass lens delivers a sharp, clear image.

Its slim and stylish design is also packed with great features, including: In-Camera Panorama Stitching, Smile Detection, Blink Detection, Face Detection, Electronic Image Stabilization, Red-Eye Removal and an amazing MPEG-4 movie recording capability. The E1235 also comes with a rechargeable lithium-ion battery for non-stop picture taking, and its memory can be expanded up to four gigabytes with SD or SDHC memory cards.

If you thought that only a professional camera could deliver resolution this great, try the GE E1235 for yourself. It will challenge your idea of what a point-and-shoot camera can do.

Shown in black.
Also available:



Red



Silver



Exclusive
Digital Camera
Licensee

General Imaging™

Megapixels aren't the only thing about this camera that's huge.

Effective Image Sensor Pixels	12.20 Megapixels	
Image Sensor	12.40 Megapixels [1/1.72" Charge Coupled Device (CCD)]	
Lens	Focal Length F = [35mm film equivalent]	7.5 mm (Wide) — 22.5 mm (Tele) [34 mm (Wide) — 102 mm (Tele)]
	F number	F2.8 (Wide) — F4.9 (Tele)
	Lens Construction	7 elements in 7 groups
	Optical Zoom	3x
	Focusing Range	Normal : 60cm~∞ Macro : (Wide) 6cm~∞, (Tele) 40cm~∞
Anti-Handshake	Electronic Image Stabilization	
Digital Zoom	4.5x digital zoom (Combined Zoom: 13.5x)	
Number of Recording Pixels	Still Image	(4:3)12MP: 4032×3024, (3:2)10MP: 4032×2688, (16:9)9MP: 4032×2268, 6MP: 2816×2112, 3MP: 2048×1536, 2MP: 1600×1200, 1MP: 1024×768, 0.3MP: 640×480
	Movie	640×480pixels: 20fps/15fps, 320×240pixels: 20fps/15fps
Image Compression	Best、Fine、Normal	
DCF、DPOF (Ver1.1) Support	Yes	
File Format	Still Image	Exif2.2 (JPEG)
	Movie	Image Compression: MPEG4, Audio: G.711 (Monoaural)
	Audio	WAVE [Monoaural] (Max 60 seconds)
Shooting Modes	Auto, Manual, Image Stabilization, Movie, Scene (Sport, Children, Indoor, Leaf, Snow, Sunset, Fireworks, Glass, Museum, Landscape, Night Landscape, Night Portrait), Panorama, Portrait	
Start-Up Time	2.4 sec.	
Detection Features	Face, Smile and Blink	
Red-Eye Removal	Yes	
GPS Support	No	
Viewfinder	-	
LCD Screen	2.7 inch (230.400 pixels) LTPS (low-temperature polycrystalline silicon) TFT color LCD	
ISO Sensitivity	Auto, ISO80/100/200/400/800/1600/3200 (3M)	
AF Method	Single AF, Multi-AF (TTL 9-point), Face-Detection, AF Assist Beam (On/Off)	
Light Metering Method	Artificial Intelligence AE (Ai AE), Center-Weighted Average, Spot (Fixed to center of frame)	
Exposure Control Method	ProgramAE (AE-lock available)	
Exposure Compensation	± 2 EV in 1/3 Step increments	
Shutter Speed	4 ~ 1/2000 second (Manual 30s)	
Continuous Shooting	Approx. 1.25 fps (Large/Fine Mode)	
Playback Modes	Single Photo, Index (4 / 9 / 16 thumbnails), Slide Show, Movie (Slow-Motion possible), Zoom (Approx. 1x~8x), Audio, Histogram Display	
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual	
Internal Flash (Shooting Range)	Auto / Red-Eye Reduction / Forced Flash / No Flash / Slow Synchro / Red-Eye Reduction+Slow Synchro	
	Shooting Range Wide: Approx. 0.3m~4.1m / Tele: Approx. 0.3m~2.3m (ISO 400)	
Recording Media	Internal Memory: 26MB	
	SD Card / SDHC Card (Up to 4GB support)	
Other Features	PictBridge、ExifPrint Support、Multi-language Support (11 languages)	
Jacks	USB2.0 / AV-OUT (Integrated Proprietary Connector), DC-IN	
Power	Rechargeable Lithium-ion Battery GB-40, 3.7V 1050mAh	
Shooting Capability (Battery Performance)	Approx. 210 shots (based on CIPA Standards)	
Operation Environment	Temperature: 0~40°C, Humidity: 0~90%	
Dimensions (W x H x D)	4.1 inch Width x 2.2 inch Height x .9 inch Depth (103mm Width x 56mm Height x 24mm Depth)	
Weight	5.1 oz. (Approx. 145g) (Body only)	
Supplied Accessories	Rechargeable Lithium-ion Battery, Battery Charger, USB Cable, AV Cable, Wrist Strap, CD-ROM, Manual, Quick Start Guide, Warranty Card	

(Design and specifications are subject to change without notice)