

G Series G2



An ultra-slim digital camera that delivers big features.

If style is what you're after, the GE G2 is certainly the right pick for you. With its lightweight design and ultra-slim 18mm metal body, this is one of the slimmest and lightest cameras on the market. The GE G2 proves once again that great things can come in small packages.

Engineered into its compact body is a whole host of advanced features. The G2 comes with eight-megapixel resolution, 4x optical zoom, 4.5x digital zoom, 18x combined zoom, and a 2.7" high-resolution LCD screen (230,400 pixels) that makes it easy to set up your snapshots and review them afterwards. The G2 also features the latest auto-brightness LCD technology that ensures perfect screen visibility both indoors and outdoors, and an aspheric all-glass lens for sharper, clearer pictures.

The G2 also comes with a user friendly mode dial and a navigation pad that makes operation fun and easy. A simple, intuitive interface makes it easy to access advanced features, including: In-Camera Panorama Stitching, Smile Detection, Blink Detection, Face Detection, Electronic Image Stabilization, Red-Eye Removal and an amazing MPEG-4 movie recording capability.

Once you hold the G2 and see everything it has to offer, you'll discover just how much value we've packed into this ultra-slim, stylish package.

Shown in black.
Also available:



Exclusive
Digital Camera
Licensee

General Imaging™

An ultra slim digital camera that delivers big features.

Effective Image Sensor Pixels	8.0 Megapixels	
Image Sensor	8.31 Megapixels [1/2.35" Charge Coupled Device (CCD)]	
Lens	Focal Length F = [35mm film equivalent]	6.75 mm (Wide) — 27 mm (Tele) [38 mm (Wide) — 152 mm (Tele)]
	F number	F3.5 (Wide) — F5.15 (Tele)
	Lens Construction	14 elements in 11 groups
	Optical Zoom	4x
	Focusing Range	Normal : (Wide) 60cm $\sim\infty$; (Tele) 80 cm $\sim\infty$ Macro : (Wide) 6cm $\sim\infty$; (Tele) 80 cm $\sim\infty$
Anti-Handshake	Electronic Image Stabilization	
Digital Zoom	4.5x digital zoom (Combined Zoom: 18x)	
Number of Recording Pixels	Still Image	8MP: 3264×2448, (3:2)7MP: 3264×2176, (16:9)6MP: 3264×1836, 5MP: 2560×1920, 3MP: 2048×1536, 2MP: 1600×1200 1MP: 1024×768, 0.3MP: 640×480
	Movie	640×480pixels: 30fps / 15fps, 320×240pixels: 30fps / 15fps
Image Compression	Best、Fine、Normal	
DCF、DPOF (Ver1.1) Support	Yes	
File Format	Still Image	Exif2.2 (JPEG)
	Movie	Image Compression: MPEG4, Audio: G.711 (Monoaural)
	Audio	WAVE (Monoaural) (Max 60 seconds)
Shooting Modes	Auto, Manual, Image Stabilization, Movie, Scene (Sport, Children, Indoor, Leaf, Snow, Sunset, Fireworks, Glass, Museum, Landscape, Night Landscape, Night Portrait), Panorama, Portrait	
Start-Up Time	1.5 sec.	
Detection Features	Face, Smile and Blink	
Red-Eye Removal	Yes	
GPS Support	No	
Viewfinder	-	
LCD Screen	2.7 inch (230.400 pixels) LTPS (low-temperature polycrystalline silicon) TFT color LCD	
	Self-regulation brightness in the sun	
ISO Sensitivity	Auto, ISO80 / 100 / 200 / 400 / 800 / 1600	
AF Method	Single AF, Multi-AF (TTL 9-point), Face-Detection, AF Assist Beam (On/Off)	
Light Metering Method	Artificial Intelligence AE (Ai AE), Center-Weighted Average, Spot (Fixed to center of frame)	
Exposure Control Method	ProgramAE (AE-lock available)	
Exposure Compensation	± 2 EV in 1/3 Step increments	
Shutter Speed	4 ~ 1/2000 second (Manual 30s)	
Continuous Shooting	Approx. 1.8 fps (Large / Fine Mode)	
Playback Modes	Single Photo, Index (4 / 9 / 16 thumbnails), Slide Show, Movie (Slow-Motion possible), Zoom (Approx. 2x~8x), Audio, Histogram Display	
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual	
Internal Flash (Shooting Range)	Auto / Red-Eye Reduction / Forced Flash / No Flash / Slow Synchro / Red-Eye Reduction+Slow Synchro	
	Shooting Range Wide: Approx. 0.3m~3.3m / Tele: Approx. 0.3m~2.7m (ISO 400)	
Recording Media	Internal Memory: 26MB	
	SD Card / SDHC Card (Up to 4GB support)	
Other Features	PictBridge、ExifPrint Support、Multi-language Support (11 languages)	
Jacks	USB2.0 / AV-OUT (Integrated Proprietary Connector)	
Power	Rechargeable Lithium-ion Battery GB-20, 3.7V 750mAh	
Shooting Capability (Battery Performance)	Approx. 200 shots (based on CIPA Standards)	
Operation Environment	Temperature: 0~40°C, Humidity: 0~90%	
Body Material	Metal Cover	
Dimensions (W x H x D)	3.6 inch Width × 2.4 inch Height × .7 ~ .8 inch Depth (91mm Width × 59.8mm Height × 18-20mm Depth)	
Weight	3.4 oz. (Approx. 95g) (Body only)	
Supplied Accessories	Rechargeable Lithium-ion Battery, Battery Charger, USB Cable, AV Cable, Wrist Strap, CD-ROM, Manual, Quick Start Guide, Warranty Card	